



TYP ANB

VÝSTUP S VNITŘNÍM ZÁVITEM

PRO OCELOVÉ TRUBKY

DIN EN 10255 a DIN EN 10220 série 1

SÉRIE 261: 17,2-114,3mm

MAX. PROVOZNÍ TLAK/TEPLOTA:

Voda: max 25 °C/max. 16 bar

Topná voda: max. 90 °C/max. 6 bar



DN	Vnější průměr trubky-Ø x spojovací závit [mm]	Výrobek č.
10	17.2 × 3/8"	01.261.28.0000
15	21.3 × 1/2"	01.261.28.0101
20	26.9 × 1/2"	01.261.28.0201
25	33.7 × 1/2"	01.261.28.0301
25	33.7 × 3/4"	01.261.28.0302
32	42.4 × 3/4"	01.261.28.0402
40	48.3 × 3/4"	01.261.28.0502
50	60.3 × 1"	01.261.28.0603
65	76.1 × 1"	01.261.28.0703

DN	Vnější průměr trubky-Ø x spojovací závit [mm]	Výrobek č.
65	76.1 × 1 1/4"	01.261.28.0704
65	76.1 × 1 1/2"	01.261.28.0705
80	88.9 × 1"	01.261.28.0803
80	88.9 × 1 1/4"	01.261.28.0804
80	88.9 × 1 1/2"	01.261.28.0805
80	88.9 × 2"	01.261.28.0806
100	114.3 × 1"	01.261.28.0903
100	114.3 × 1 1/4"	01.261.28.0904
100	114.3 × 1 1/2"	01.261.28.0905
100	114.3 × 2"	01.261.28.0906

ROZMĚRY A VÁHY

DN	Výstupný závit Rp ISO 7/1	PRO OCELOVÉ TRUBKY		Délka				
		Vnější průměr trubky-Ø [mm]	Hmotnost [kg]	~A [mm]	~B [mm]	~C [mm]	~D [mm]	~E [mm]
10	3/8"	17.2	0.2	70	28	53	36	22
15	1/2"	21.3	0.3	70	33	60	50	31
20	1/2"	26.9	0.4	70	40	70	55	32
25	1/2"	33.7	0.5	70	46	74	61	37
25	3/4"	33.7	0.5	70	46	74	61	37
32	3/4"	42.4	0.6	80	57	86	75	45
40	3/4"	48.3	1.0	100	66	94	85	48
50	1"	60.3	1.2	100	80	109	100	60
65	1"	76.1	2.0	100	100	140	115	65
65	1 1/4"	76.1	2.0	100	100	140	115	65
65	1 1/2"	76.1	2.0	100	100	140	115	65
80	1"	88.9	2.4	100	115	150	131	75
80	1 1/4"	88.9	2.4	100	115	150	131	75
80	1 1/2"	88.9	2.4	100	115	150	131	75
80	2"	88.9	3.2	135	115	150	136	75
100	1"	114.3	2.9	100	140	187	160	90
100	1 1/4"	114.3	3.3	100	140	187	160	90
100	1 1/2"	114.3	3.3	100	140	187	160	90
100	2"	114.3	4.4	135	140	187	165	90

TŘMEN S NAVRTÁVKOU PRO OCELOVOU TRUBKU

17,2 mm – 114,3 mm

